

STRONG POLES

THE SECURITY INDUSTRY STANDARD

Strong Poles LED Light Fixtures

Part Numbers:
SP-LED150W
SP-LED265W

150W and 265W
Lights Ready to ship!



Occupancy & daylight sensor
Included with every light

Compatible with all Strong Poles 2 3/8" tenon mounts

100-277V AC required

5000k Temp Standard

Day Night Sensors AND shorting caps included with every light

Type 4 Beam Angle Standard 130°x75°

Incredibly thin and light-weight aerodynamic design

LED lifetime of more than 50000 hours

Optional Wattages, Temps, Mounts and Beam Angles available for Special Order!

Specifications **SP-LED150W**

400-500W Traditional Light Replacement

Electrical Specifications

Nominal Wattage:	150W
Nominal Voltage:	100-240/277VAC or 277-528VAC
Maximum Current:	AC 1.67A (max)
Power Factor (PF):	>0.95
Driver Efficiency:	>94%

Photometric Specifications

Luminous Flux:	Lumen tolerance +/- 5% up to 19500lm
Color Rendering Index:	Ra>70 or Ra>80
Color Temperatures:	3000-6500K
Optional Beam Angles:	70°/130° / 75°/150° / 120°, etc

Mechanical Specifications

IP&IK Rating:	IP66 & IK10
Lifetime (L70 Standard):	>50000 hours
Heat Radiator:	Anodized Aluminum
Lens Material:	Optical level polycarbonate
Fixture Dimension:	560*278*75mm 22*10.9*2.95 inches
Net Weight:	5.6kg
Carton Dimensions:	665*353*135mm
Gross Weight:	6.7kg

Specifications **SP-LED265W**

1000W Traditional Light Replacement

Electrical Specifications

Nominal Wattage:	265W
Nominal Voltage:	100-240/277VAC or 277-528VAC
Maximum Current:	AC 2.95A (max)
Power Factor (PF):	>0.95
Driver Efficiency:	>95%

Photometric Specifications

Luminous Flux:	Lumen tolerance +/- 5% up to 34450lm
Color Rendering Index:	Ra>70 or Ra>80
Color Temperatures:	3000-6500K
Optional Beam Angles:	70°/130° / 75°/150° / 120°, etc

Mechanical Specifications

IP&IK Rating:	IP66 & IK10
Lifetime (L70 Standard):	>50000 hours
Heat Radiator:	Anodized Aluminum
Lens Material:	Optical level polycarbonate
Fixture Dimension:	637*350*75mm 25.1*13.8*3 inches
Net Weight:	9.35kg
Carton Dimensions:	750*440*180mm
Gross Weight:	10.8kg

- **UL Listed**
- **Super thin**
- **5 yr warranty**

1-844-669-3537